

Tensar Declaration of Performance Tensar RE560 Geogrid



1) Unique identification code of the product type:

RE560

2) Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Geogrid RE560 - Batch number is provided on the product packaging

3) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use in construction of earthworks, foundations and retaining structures, reservoirs and dams, canals, solid waste disposal and liquid waste containment.

Intended use: Reinforcement

4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Manufactured in Factory A
Tensar Manufacturing Limited
Sett End Road West
Shadsworth Business Park
Blackburn
BB1 2PU
United Kingdom

Tel: +44 (0) 1254 262431 Fax: +44 (0) 1254 266867 E-mail: sales@tensar.co.uk Manufactured in Factory B
Tensar Geosynthetics (China) Limited
289 Checheng Avenue
Wuhan Economics Development Zone
Hanyang District
Wuhan
China 430056
Tel: +86 27 8423 6370

Fax: +86 27 8423 6381

E-mail: marketing@tensar.com.cn

5) System or systems of assessment and verification of constancy of performance of the construction product as set out in the CPR, Annex V:

System 2+

Last two digits of year of affixing CE marking - 08

6) In case of the declaration of performance concerning a construction covered by a harmonised

Notified certification body KIWA No – 0799 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

Warning - This Declaration of Performance is made available to a customer of Tensar International with respect to geogrid supplied under a contract of sale.

Improper use of the document includes the comparison of products for the purpose of claiming 'equivalence' both generally and for an unrelated project.



Tensar Declaration of Performance Tensar RE560 Geogrid

7) Declared performance:

Performance R	elated Physical F	Properties of the	Geogrid	Harmonised Technical Specification
Essential characteristic		Performance		•
Product characteristic	Unit of characteristic	Declared Value	Tolerance	
Tensile Strength (EN ISO 10319)	kN/m	MD – 93,0	-4,3	EN13251:2000 + A1:2005 EN13254:2000 + A1:2005
Elongation at Maximum Load (EN ISO 10319)	%	MD – 11,0	±3,0	
Static Puncture (CBR test) (EN ISO 12236) a	kN	NPD	NPD	
Dynamic Perforation Resistance (cone drop test) (EN ISO 13433) ^a	mm	NPD	NPD	
Tensile creep (EN ISO 13431)	kN/m	Long term creep rupture strength at a design life of 120 years and 10°C in soil temperature is 45,9kN/m		EN13255:2000 + A1:2005 EN13257:2000 + A1:2005 EN13265:2000 + A1:2005
Damage During Installation (BS8006, EN ISO 10722-1)	%	Retained Strength >80%	-0	
Dangerous substances (National Regulations in force in EU Member States)		Less than required by national regulations in EU Member States		
Durabi	lity Statement (El	N 13251, Annex B	3)	
The minimum working life between 4 and 9 and in soi (Rep No BAM VI 33/5099/07,ERA	I temperatures less that		•	

^a This test is not applicable for geogrids.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer in point 4. Signed for and on behalf of the manufacturer by:

Name: Steven Howard Function: Quality Manager Date of Issue: 21/09/2017

Signature: S. Howard.

Tensar is a registered trade mark

Tensar Manufacturing Limited

Tel: **+44 (0) 1254 262431** Fax: +44 (0) 1254 266867 E-mail: sales@tensar.co.uk www.tensar-international.com **UK Head Office Sett End Road Shadsworth Business Park Blackburn BB1 2PU United Kingdom**

