

# Tensor Declaration of Performance Tensor AR1 Geogrid



- 1) Unique identification code of the product type:  
**AR1**
- 2) Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):  
**Geogrid AR1 – Batch number is provided on the product packaging**
- 3) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**For use in construction of Pavements and asphalt overlays  
Intended use: Reinforcement**
- 4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):  
**Manufactured in Factory A**  
**Tensor Manufacturing Limited**  
**Sett End Road West**  
**Shadsworth Business Park**  
**Blackburn**  
**BB1 2PU**  
**United Kingdom**  
Tel: **+44 (0) 1254 262431**  
Fax: **+44 (0) 1254 266867**  
E-mail: [sales@tensar.co.uk](mailto:sales@tensar.co.uk)
- 5) System or systems of assessment and verification of constancy of performance of the construction product as set out in the CPR, Annex V:  
**System 2+**  
Last two digits of year of affixing CE marking – 10
- 6) In case of the declaration of performance concerning a construction covered by a harmonised standard:  
**Notified certification body KIWA No – 0799 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.**

**Warning** - This Declaration of Performance is made available to a customer of Tensor International with respect to geogrid supplied under a contract of sale.

Improper use of the document includes the comparison of products for the purpose of claiming 'equivalence' both generally and for an unrelated project.

# Tensar Declaration of Performance Tensar AR1 Geogrid

7) Declared performance:

Performance Related Physical Properties of the Geogrid				Harmonised Technical Specification
Essential characteristic		Performance		<b>EN 15381:2008</b>
Product characteristic	Unit of characteristic	Declared Value	Tolerance	
Tensile Strength (EN ISO 10319)	kN/m	MD – 22 CMD – 22	-2 -2	
Elongation at Maximum Load (EN ISO 10319)	%	MD – 11 CMD – 11	± 4 ± 4	
Static Puncture Resistance (CBR test) (EN ISO 12236) <sup>a</sup>	kN	NPD	NPD	
Dynamic Perforation Resistance (cone drop test) (EN ISO 13433) <sup>a</sup>	mm	NPD	NPD	
Melting Point (EN 3146)	°C	Melting point of the geogrid = 168°C	-0	
Dangerous substances (National Regulations in force in EU Member States)		Less than required by national regulations in EU Member States		
<b>Durability Statement (EN 15381, Annex B)</b>				
To be covered within 30 days in accordance with EN 12224.				
>90% retained strength in accordance with EN 14030. Alkaline only (Rep No 10/11391/LP)				

<sup>a</sup> This test is not applicable for geogrids.

8) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer in point 4. Signed for and on behalf of the manufacturer by:

Name: Steven Howard  
Function: Quality Manager  
Date of Issue: 26/11/2015

Signature: 

Tensar is a registered trade mark

<p><b>Tensar Manufacturing Limited</b></p> <p>Tel: +44 (0) 1254 262431 Fax: +44 (0) 1254 266867 E-mail: <a href="mailto:sales@tensar.co.uk">sales@tensar.co.uk</a> <a href="http://www.tensar-international.com">www.tensar-international.com</a></p>	<p><b>UK Head Office</b> <b>Sett End Road</b> <b>Shadsworth Business Park</b> <b>Blackburn</b> <b>BB1 2PU</b> <b>United Kingdom</b></p>	
---	---	---